LGT 4725

MediLine

Gross/net capacity	441/418 litre
Ext. dimensions in mm (w/d/h)	1653/789/915
Int. dimensions in mm (w/d/h)	1445/500/650
Energy consumption in 365 days	1589 kWh
Climate rating	4 ¹
Refrigerant	R 290
Airborne acoustical noise emissions	55 dB(A)
Connection Rating	3.5 A
Voltage	220-240 V~
Cooling system	static
Defrosting	manual
Temperature range	-10°C to -45°C
Gradient *	3.5°C
Max. fluctuation **	1.8°C
Lid material	Steel
Housing material/colour	steel/white
Liner Material	white-coated aluminium
Type of Control	electronic controller
Temperature display	außen digital
Interface	RS 485
volt-free alarm contact	yes
Maximum number of baskets	16
Handle	aluminium shape
Lock	fitted
Insulation	100 mm
Defrost water drain	yes
Gross/net weight	91 / 77 kg
EAN-Nr.	9005382201152



1 Climate class / Climate Rating: SN +10°C to +32°C

3 +10°C to +25°C

ST +16°C to +38°C

5 +10°C to +40°C

T +16°C to +43°C

7 +10°C to +35°C

Subject to modification. Timestamp: 20.06.2018

* Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration. ** Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.

N +16°C to +32°C

4 +10°C to +30°C

