LGex 3410

MediLine



Gross/net capacity	310/284 litre
Ext. dimensions in mm (w/d/h)	597/615/1840
Int. dimensions in mm (w/d/h)	420/400/1587
Energy consumption in 365 days	478 kWh
Climate rating	7 1
Refrigerant	R 600a
Airborne acoustical noise emissions	45 dB(A)
Connection Rating	1.5 A
Voltage	220-240 V~
Cooling system	static
Defrosting	manual
Temperature range	-9°C to -30°C
Gradient *	6.9°C
Max. fluctuation **	4.2°C
Housing material/colour	steel/white
Door/lid material	Steel
Liner Material	moulded polystyrol white
Type of Control	electronic controller
Temperature display	außen digital
Fault: warning signal	visual and audible
Interface	RS 485
volt-free alarm contact	yes
Number of drawers	8
Maximum number of baskets	8
Shelves	8
Shelf material	evaporator plates
Shelf loading	24 kg
Handle	Ergonomic door handle
Lock	fitted
Self-closing door	yes
Door hinges	right, reversible
Insulation	77-65 mm
Gross/net weight	92 / 86 kg
EAN-Nr.	9005382197271

1 Climate class / Climate $R\overline{a}$ ting: SN +10°C to +32°C

N +16°C to +32°C

ST +16°C to +38°C

T +16°C to +43°C

³ +10°C to +25°C

^{4 +10°}C to +30°C

⁵ +10°C to +40°C

^{7 +10°}C to +35°C

^{*} Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

** Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.