



VELOCITY 15µ

High Speed Microcentrifuge

Features & Characteristics

- Maximum speed 15,000rpm (21,380 xg)
- Choices of rotors for 24 x 0.2/0.5/1.5/2.0ml tubes, 18 x 5ml tubes, 36 x 0.5ml tubes and 4x 8-strip PCR tubes
- Autoclavable Bio-safe rotors
- Advanced air-cooling technology to lower rotor temperature for model Velocity 15µ
- Automatic lid release after run
- Dual door interlock safety design
- User-friendly control panel with large LCD display



VELOCITY 13µ

Mini Fuge

Features & Characteristics

- Maximum speed 13,500rpm (12,300 xg)
- Choices of rotors for 12 x 1.5/2.0ml tubes and 32 PCR tubes or strips
- Compact design
- Rapid acceleration (≤ 12 sec) and deceleration (≤ 16 sec)
- Autoclavable rotor
- Safe operation with lid-lock function
- User-friendly control panel with LCD display

VELOCITY 15µ & 13µ Specifications

VELOCITY 15µ SPECIFICATIONS	Velocity 15µ	Velocity 13µ
Maximum Speed	15,000 RPM	13,500 RPM
Maximum RCF	21,380 x g	12,300 x g
Run Time	30 seconds to 99 minutes or HOLD (Continuous)	Up to 30 mins or HOLD (Continuous)
Rotor (Standard)	24 x 1.5/2.0 ml tubes	12 x 1.5/2.0 ml tubes
Rotor (Optional)	18 x 5 ml tubes, 36 x 0.5 ml tubes, 4 x 0.2ml 8-strip PCR tubes	32 x 0.2 ml PCR tubes or strips
Noise Level	≤ 58 dB	≤ 56 dB
Dimensions (w x d x h)	280 x 364 x 266 mm	208 x 245 x 145 mm
Weight	12 kg	4.4 kg
Power Supply	AC 200-240V 50/60Hz or AC 110-120V 50/60Hz	AC 200-240V 50/60Hz or AC 110-120V 50/60Hz



The VELOCITY Range

MICROCENTRIFUGES

Headquarters

Dynamica Scientific Ltd.

Unit 12 Cromwell Business Centre,
Howard Way, Newport Pagnell,
MK16 9QS, United Kingdom

P: +44(0)1908 211 900

F: +44(0)1908 211 909

Email: info@dynamica-eu.com

Australasia

Dynamica Pty Ltd

Unit C3 Hallmarc Business Park
Corner Centre and Westall Roads
Clayton, Victoria, 3168, Australia

P: +61 3 8540 5988

F: +61 3 9548 7177

Email: info@dynamica.com.au

Asia

Dynamica (Asia) Limited

6/F., Mita Ctr.,
552-566 Castle Peak Rd.,
Kwai Chung, Hong Kong

P: +852 3583 1581

F: +852 3583 1580

Email: info@dynamica-asia.com