

MKv 3913

LED

MediLine



Gross/net capacity	386/278 litre
Ext. dimensions in mm (w/d/h)	600/615/1840
Int. dimensions in mm (w/d/h)	440/435/1635
Energy consumption in 365 days	480 kWh
Climate rating	4 ¹
Refrigerant	R 600a
Airborne acoustical noise emissions	48 dB(A)
Connection Rating	1.5 A
Voltage	220-240 V~
Cooling system	forced-air
Defrosting	automatic
Temperature range	+5°C
Gradient *	6.1°C
Max. fluctuation **	3.9°C
Housing material/colour	steel/white
Door/lid material	Insulated glazed door
Liner Material	moulded polystyrol white
Type of Control	electronic controller
Temperature display	external digital
Interior light	LED
Fault: warning signal	visual and audible
Interface	RS 485
volt-free alarm contact	yes
Adjustable Shelving	5
Shelf material	grid shelves plastic-coated
Shelf loading	45 kg
Handle	Ergonomic door handle
Lock	fitted
Self-closing door	yes
Door hinges	right, reversible
Insulation	40 mm
Gross/net weight	92 / 85 kg
EAN-Nr.	9005382197035

1 Climate class / Climate Rätting: **SN** +10°C to +32°C **N** +16°C to +32°C **ST** +16°C to +38°C **T** +16°C to +43°C
3 +10°C to +25°C **4** +10°C to +30°C **5** +10°C to +40°C **7** +10°C to +35°C

* Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

** Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.

Subject to modification. Timestamp: 10.09.2018

LIEBHERR